





800 x 600 mm






Art. no. 83170811

Technical data			
Dimensions L x W x H (mm)	800 x 600 x 160		
Weight (kg)	9.0		
Material* ²	PE		
Load capacity (kg)	Static 2000 kg	Dynamic 500	In Racking System -
Characteristics		Options	
Colour: light grey Runners: 2, unwelded		Central box retaine Rim options	rs
Rims: 7 mm Temperature stability: -30 °C to +40	o°C, briefly up to +90°C		
Loading quantities (Pcs / Approx	imate amount)		
Container	Container 20': 384 Container 40': 780		Container 40' High Cube: 880 Conventional trailer 45' high cube container: 1020
Truck	MEGA-Trailer: 1224		Jumbo: 1368
Labelling			



Customised printing and numbering available on request depending on quantity. Position upon consultation.









- All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- Our service team is pleased to be at your disposal if you require exact information about material compositions.
- Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C. Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.
 In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20°C.